




### Overview

This industrial grade **Super Mini Tag** is specially designed for specific RFID application with mini size and outstanding RF performance, can be fixed or embedded into some product's case, housing or stuff.

Shipping can be in form of Individual Tag, Stripped Tags with tape laminated or Tags in Reel.



### Product Spec

<b>Tag Dimension</b>	13.3 x 13.6 mm ( specific dimension on request)
<b>Tag Thickness</b>	0.50±0.03mm (depends on request)
<b>Operation Temperature</b>	-40°C ~ 85°C
<b>RF Frequency / Protocol</b>	13.56 MHz / ISO 15693
<b>RFID Chip</b>	NXP ICODE SLIX-S, or any HF Series on request
<b>Chip Spec</b>	User Memory 1280 bits, others refer to chip datasheet
<b>RFID Antenna</b>	Ni,Au plated
<b>Substrate Material</b>	Epoxy Glass Tape in web form
<b>Optional Request</b>	Serial or sequential numbers printed on tag
<b>Shipping Form</b>	1) Individual Tag 2) Strip Tags in perforated & covered with double-sided tape adhesive on side of antenna substrate 3) Reel Tag

### Application

*RFID Applications are variable. Super Mini Tag will bring us more?*



Jewelry Retail Management



Asset Life Span Management

