

UCODE EPC G2

UHF RFID Smart Label IC

The UCODE EPC G2 IC is a dedicated chip for passive, intelligent tags and labels supporting the EPCglobal class 1 gen2 standard. It is especially suited for supply chain management and logistics applications where operating distances of several meters and high anti-collision rates are required.



Key features

- Interface fully compatible with UHF EPC G2 standard
- Long-range solutions (up to 7 m in the US and 6.6 m in Europe)
- Suitable for UHF RFID, allowing one tag to be used worldwide
- Fast data rate
 - forward link: 40 - 160 kbits/s
 - return link: 40 - 640 kbits/s
- Multi-label operation at 600 tags/sec in Europe, 1600 tags/sec in the US
- 512 bits of on-chip memory
 - 96 bits EPC
 - 32 bits Tag Identifier
 - 128 bits programmable user memory
 - 32 bits access password
 - 32 bits kill password
- Runs on the same hardware infrastructure as the UCODE HSL and the UCODE EPC1.19

Semiconductors

Key benefits

- Tags / labels and readers available from various suppliers
- First UHF EPC product operating worldwide
- Highly advanced anti-collision and highest identification speed
- Reliable and robust RFID technology suitable for dense reader and noisy environment
- Secure UHF communication; readers do not transmit EPC data
- Broadest industry back-up – EPCglobal and ISO 18000-6C
- Reader portfolio covers all regional demands

The UCODE EPC G2 IC is the first UHF EPC product from Philips. Designed specifically for long-range applications, the entire UCODE family also offers anti-collision and collision arbitration functionality. This allows a reader to simultaneously operate multiple labels / tags within its antenna field.

A UCODE EPC G2 based label / tag requires no external power supply. Its contactless interface generates the power supply via the antenna circuit by propagative energy transmission from the interrogator (read/write device), while the system clock is generated by an on-board oscillator. Data transmitted from interrogator to label / tag is demodulated by the interface, and it also modulates the interrogator's electromagnetic field for data transmission from label / tag to interrogator.

A label / tag can be operated without the need for line of sight or battery, as long as it is connected to a dedicated antenna for the targeted frequency range. When the label / tag is within the interrogator's operating range, the high-speed wireless interface allows data transmission in both directions.

Key applications

- Supply Chain Management
- Asset Management
- Container Identification
- Pallet & Case Tracking

PHILIPS

UCODE EPC G2

UHF RFID Smart Label IC



Standards compliance

The UCODE EPC G2 complies with the following Air Interface standards:

- EPCglobal class 1 gen2
- ISO 18000-6C

Operating distances

For UCODE EPC G2 based tags and labels in released frequency bands

Frequency range	Region	Available power	Read range ^{1 2}
869.4 - 869.65 MHz (UHF)	Europe ³	0.5 W ERP	3.3 m
865.6 - 867.6 MHz (UHF)	Europe ⁴	2 W ERP	6.6 m
902 - 928 MHz (UHF)	America ⁵	4 W EIRP	7.0 m

Notes:

1. These read distances are typical values for general tags and labels. Practical usable values may be lower due to damping by object materials and environmental materials. A special tag antenna design can help achieve higher values.
2. Maximum write distance is approximately 70% of the read distance.
3. CEPT / ETSI EN 330 220
4. CEPT/ ETSI EN 302 208
5. FCC regulations, Part 15 Section 247

Ordering information

Order no.	Delivery type description
SL3ICS1001FW/V1	Bumped, sawn wafer on ffc, 150 µm, inked and mapped
SL3FCS1001DV/DH	IC on flip chip package in reel format
SL3S1001FTT	TSSOP8

Philips Semiconductors

Philips Semiconductors is a worldwide company with over 100 sales offices in more than 50 countries. For a complete up-to-date list of our sales offices please e-mail sales.addresses@www.semiconductors.philips.com. A complete list will be sent to you automatically. You can also visit our website <http://www.semiconductors.philips.com/sales>.

© Koninklijke Philips Electronics N.V. 2005

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.



Date of release: April 2005
Document order number: 9397 750 14922

Published in The Netherlands